

AZPLED/1

Z LED Linear 1



Features

Powerful and durable surface mounted IP65 linear high bay, perfect for the demands of industrial applications

Surface mounting possible with AZPLED/LC accessory

1.5m Suspension kit supplied as standard

Die-cast aluminium construction provides enhanced thermal performance for longer LED lifespan

Plug and play microwave sensor option, offering maximum energy saving

0/1-10V dimmable as standard (installer must drill through pilot hole and use an IP rated gland on install)

General Information

Lamp Type	LED
Colour / Finish	Black
Dimmable	Yes
IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface,Suspended
Lifetime (Hrs)	L80 B10 54,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	658 mm
Width (mm)	147 mm
Height (mm)	134 mm
Accessories	AZPLLED/MWS, AZPLLED/LC, AZPLLED/MWSP

Technical Information

Wattage	100W
Lumens Delivered	14000lm
Lm/W	140lm/W
Beam Angle	25/115
CRI	80
CCT	5000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-30°C to 40°C
SDCM	5

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:11 AM



