



## AZPLED/2

Z LED Linear 2



## Features

Powerful and durable surface mounted IP65 linear high bay, perfect for the demands of industrial applications

Surface mounting possible with AZPLED/LC accessory

1.5m Suspension kit supplied as standard

Die-cast aluminium construction provides enhanced thermal performance for longer LED lifespan

Plug and play microwave sensor option, offering maximum energy saving

0/1-10V dimmable as standard (installer must drill through pilot hole and use an IP rated gland on install)

## General Information

<b>Lamp Type</b>	LED
<b>Colour / Finish</b>	Black
<b>IP Rating</b>	IP65
<b>IK Rating</b>	IK08
<b>Class Protection</b>	1
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Surface,Suspended
<b>Lifetime (Hrs)</b>	L80 B10 54,000h
<b>Warranty (Years)</b>	5
<b>CE Mark</b>	Yes
<b>Length (mm)</b>	890 mm
<b>Width (mm)</b>	147 mm
<b>Height (mm)</b>	134 mm
<b>Accessories</b>	AZPLLED/MWS, AZPLLED/LC, AZPLLED/MWSP

# Technical Information

<b>Wattage</b>	150W
<b>Lumens Delivered</b>	21000lm
<b>Lm/W</b>	140lm/W
<b>Beam Angle</b>	25/115
<b>CRI</b>	80
<b>CCT</b>	5000K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-30°C to 40°C
<b>SDCM</b>	5

Datasheet generated from <https://onetimepim.com> last updated Monday, July 25, 2022 11:43:46 AM



